

GPS Actuator

By Bernard Controls

The best way to find your electric actuation solution



Protection for explosive atmosphere

- Electric actuators working in explosive atmosphere require a specific enclosure protection submitted to dedicated certification.
- According to market areas, there exists several types of explosion proof certifications:
 - European ATEX
 - International IECEx
 - US NEMA 7 & 9
 - Customs Union for Belarus, Kazakhstan and Russia
 - INMETRO for Brazil
 - CQST for China...

Focus on ATEX European Directive

The European directive 94/9/CE states the conditions to be met for equipment items used under potentially explosive atmosphere. It classifies the installation areas according to groups and categories:


Ex de

OR

Equipment with electric connection in increased safety "e" (tight terminal box). The remaining parts of the electric equipment are in explosion proof "d" enclosure.

Explosion proof actuator. **Ex de**


<http://www.gpsactuator.com/>



Ex d

Protection by explosion proof enclosure. Connection is achieved inside the enclosure. Enclosure is resistant to internal explosion without flame path.

Explosion proof actuator. **Ex d**



II B

Group I : Equipment for underground mining.

Group II : Equipment for explosive atmosphere other than mining.

A: butane, propane,...

B: ethylene,...

C: hydrogen, acetylene

T4

Maximum surface temperature.

T1 = 450 °C

T2 = 300 °C

T3 = 200 °C

T4 = 135 °C

T5 = 100 °C

T6 = 85 °C

Our explosion proof products have been designed for use in GROUP II, Category 2 G (D) areas.

These products shall, among other requirements, undergo a CE type examination corresponding to the sections of the CENELEC standards EN 60079, 61241, 13463

<http://www.gpsactuator.com/>

applicable for each product.

BERNARD CONTROLS can offer different levels of protection such as : Ex de, Ex d, IIB, IIC, T4, T5, T6.

Focus on North American standards: NEMA ratings

NEMA Class	Group	Division	T
7	I Combustible gases and vapours	Group B: Hydrogen Group C: Ether, Ethylene,... Group D: Butane, Propane,...	1 Normal conditions Maximum surface temperature.
9	II Combustible dusts	Group E: Metal dust Group F: Coal dust Group G: Flour and other dusts	2 Abnormal conditions T1 = 842 °F T2 = 572 °F T3 = 392 °F T4 = 275 °F T5 = 212 °F T6 = 185 °F

Explosion proof actuator **NEMA 7 or NEMA 9**